

- NOTES:
1. MAX. INSTALLATION TORQUE: 6in-lbs.
 2. MOUNTING HOLE DIA.: .228
 3. HARDWARE IS INCLUDED.
 4. THIS IS A LEAD FREE PART.
 5. MAX. REFLOW IS 245°C FOR 5 SEC.



02


LEAD FINISH: SOLDER	
BUSHING FINISH: SILVER	
CAPACITANCE	4000 pF MIN.
TEMP. RANGE	-55°C TO 125°C
CURRENT	10 AMP MAX.
WORKING VOLTAGE	85°C 500 VDC MAX. 125°C 300 VDC MAX.
D.C. RESISTANCE	.01ohms MAX.
MIN. I.L. PER MIL-STD-220 AT 25°C NO LOAD	
FREQ. MHz	I.L. (db)
10	15
30	30
100	65
300	70
1 GHz	70

SCHEMATIC



MARKING:

PART: SF001
 BAG:
 1221F-001
 DATE CODE
 LOT NO.
 QTY./BAG (100 MAX.)

	02	01	00	REV. NO.	TOLERANCES UNLESS OTHERWISE SPECIFIED	 SPECTRUM CONTROL INC.	FAIRVIEW PENNSYLVANIA
	CN 36348-ENG	CN 30483-CPD	CN 23380-CPD	CHANGE NOTICE	Fractions ± 1/32		
					Dec. .xx±	Date 7-24-07	RESIN SEAL FILTER
					Dec. .xxx±.015	Engr. SACKETT	1221F-001
					Angles ±0° 30'	Scale NONE	
					CODE IDENT. NO. 0LSP2		

